## SHEDS/ACCESSORY STRUCTURES



PRIOR TO SUBMISSION OF APPLICATION FOR A SHED OR ACCESSORY STRUCTURE, A SITE/PLOT PLAN NEEDS TO BE SUBMITTED FOR ZONING APPROVAL.

SHEDS/ACCESSORY STRUCTURES MUST BE LOCATED A MINIMUM OF TEN (10) FEET FROM THE HOUSE OR PRIMARY STRUCTURE IN REAR OF PROPERTY.

## **SHEDS**

- MAXIMUM SHED SIZE IS 144 SQUARE FEET
- MAXIMUM SHED HEIGHT IS TEN (10) FEET
- ONE SHED PER LOT.
- SETBACK RESTRICTIONS FROM SIDE AND/OR REAR LOT LINES:
  - R-1 THREE (3) FEET R-2 TWO (2) FEET R-3 TWO (2) FEET
- MAY BE PLACED ON A CONCRETE SLAB NOT LESS THAN FOUR (4) INCHES THICK.
- MAY BE PLACED ON FOUR (4) INCHES OF CRUSHED STONE.
- SHED MUST CONTAIN TREATED SKIDS THAT ELEVATE THE FLOOR FOUR (4) INCHES ABOVE CRUSHED STONE.

## **ACCESSORY STRUCTURES**

- ACCESSORY STRUCTURES SETBACK IS 5 FEET FROM ALL PROPERTY LINES.
- SIZE RESTRICTIONS PER ORDINANCE 1292.06 ACCESSORY STRUCTURES

ACCESSORY STRUCTURES SHALL NOT EXCEED 8% OR THE PARCEL'S OVERALL DISTRICT THRESHOLD FOR BUILDING COVERAGE OR LOT IMPRERVIOUSNESS

• MAXIMUM HEIGHT IS FIFTEEN (15) FEET